

Resistance/Temperature table for Meitav-tec sensors (NTC 50KΩ@25°C)

*Nominal resistance values

T(°C)	R(KΩ)	T(°C)	R(KΩ)	T(°C)	R(KΩ)	T(°C)	R(KΩ)	T(°C)	R(KΩ)
-30	833.8	-4	197.6	21	59.68	48	19.38	74	7.519
-29	785.6	-3	187.8	22	57.08	49	18.65	75	7.267
-28	740.5	-2	178.5	24	52.24	50	17.94	76	7.025
-27	698.2	-1	169.7	25	50	51	17.27	77	6.791
-26	658.6	0	161.3	26	47.86	52	16.62	78	6.567
-25	621.4	1	153.5	27	45.83	53	16	79	6.351
-24	586.6	2	146	28	43.89	54	15.41	80	6.143
-23	553.8	3	139	29	42.05	55	14.84	81	5.942
-22	523.1	4	132.3	30	40.29	56	14.29	82	5.749
-21	494.2	5	126	31	38.61	57	13.77	83	5.563
-20	467.1	6	120	32	37.02	58	13.27	84	5.384
-19	441.7	7	114.4	33	35.49	59	12.79	85	5.212
-18	417.7	8	109	34	34.04	60	12.33	86	5.045
-17	395.2	9	103.9	35	32.65	61	11.89	87	4.885
-16	374	10	99.06	36	31.33	62	11.47	88	4.731
-15	354.1	11	94.48	37	30.07	63	11.06	89	4.582
-14	335.3	12	90.14	38	28.86	64	10.67	90	4.438
-13	317.6	13	86.02	39	27.71	65	10.29	91	4.3
-12	300.9	14	82.1	40	26.61	66	9.934	92	4.166
-11	285.2	15	78.39	41	25.56	67	9.588	93	4.038
-10	270.4	16	74.86	42	24.55	68	9.256	94	3.913
-9	256.5	17	71.51	43	23.59	69	8.937	95	3.793
-8	243.3	18	68.32	44	22.67	70	8.631	96	3.678
-7	230.9	19	65.29	45	21.8	71	8.336	97	3.566
-6	219.1	20	62.42	46	20.95	72	8.053	98	3.458
-5	208.1	23	54.6	47	20.15	73	7.781	99	3.354